

# One way galvanised Tipper

## Details

**Price:** \$8,512 Inc. GST  
**Dealer Stock #:** 2015 T2  
**New / Used:** Dealer New



## Seller Details



**Name:** A2B Trailers  
**Phone:** (02) 8311 4254  
**Dealer** 058440  
**License No:**  
**State:** NSW  
**Suburb:** Erina  
**Postcode:** 2250

## Description

Dimensions and weights Internal size (LxWxH) 254x145x35 cm Total size (LxWxH) 397x150x107 cm Loading height 72 cm Total weight 2,000 kg Payload 1,120 kg Tip angle, Back tip 50 degrees Body Wheel 4 PCs, 195 /50R13 " Compact Radials Axles 2 PCs, with brake Sides - material Aluminium Bottom Hot-Dip Galvanized steel plate Standard Equipment Parabolic leaf springs -Yes Heavy duty Jockey wheel -Yes Electric Hydraulic Tip -Yes Cord-held remote control -Yes Galvanized Steel Base -Yes 13 or 7-Pin Plug -Yes Interior lashing Hooks - 6 pcs. Opening/detachable sides -Yes, all 4 Detachable Corner posts-Yes Ramp drawers under bed - Yes Amber side safety reflectors Electric battery multi-charger/socket + attachments Easy load hinge system # Mesh sides available Available for delivery in Australia Wide. Extremely lightweight, durable and safe in design. Excludes stamp duty, rego or transport from sales warehouse to client. For more information Email or call the number attached. Why Variant.. At A2B Trailers we believe in providing customers with the highest quality and utmost safety. The features of our trailers are unmatched by competitors and truly the best in the industry. Tyres All our Variant Trailers Use E4-rated Tubeless radials. A radial bull features transverse radial plies, that run perpendicular to the direction of travel, this assures less heat build-up and a softer ride. Our tyres are C-rated for fuel efficiency, driving in wet conditions and sound rating ' Medium'. Rolling resistance (A-G) – This measurement of fuel efficiency for the vehicle's rolling resistance. The energy lost when the tyre is rolling on the road surface, the lower the resistance the greater the fuel reduction and CO2 levels. A is the best-performing and G is the lowest. Wet Grip (A-G) provides A sliding scale with information regarding the Grip ability of a tyre in wet conditions. Higher-performance tyres in this category would have shorter braking distances as the longer two lower-performing ratings. A indicates the highest performance and G the lowest. Noise (67-79 Db) – This measures the amount of noise the tyre generates. Usually on the tyre label itself, one black wave indicates the least amount of noise generated from the tyres. Three waves mean the highest amount of noise. This is measured in decibels. The higher the Db the greater the noise level. Suspension Our trailers will use either a Knott suspension system or axle leaf spring systems for greater road stability. These are used in conjunction with either solid steel beam axles or rubber & steel compression axles. Braking All our spread-lever have an auto-reverse within the hub. With the overrun system – the hydraulically dampened overrun control device is made up of six main elements that control and operate the following system. Safety Skid The safety skid is an integral feature of the cast housing and protects the overrun liver and handbrake liver from damage from sleeping policemen and other objects under the trailer" Ease of Use The Variant/Knott Hitch coupling enables easy manoeuvring of the trailer, by not using a towing eye or handbrake lever which often leads to damage or dirty hands. Night Light All our trailers come as standard with white reverse light lenses for safe reversing and enhanced viewing through mirrors or reversing cameras. It also illuminates the area in the direction you want people to be aware of your driving. Strength You need to have absolute confidence in your trailer, that's why we develop the very strongest and sturdiest trailers. We also have the lightest trailers in each class due to our unique thick profiled aluminium sides. 'Danish quality and design, European style and strength – 'World class'

## Product Details

Price	\$8,512
Type	Dealer New
Year	2025
Model	2015T2
Registration Date	N/A

## Further Details

Axle Configuration	Dual Axle
ATM	2000
Tare	620
Suspension	
Wheels	4
Axles	2
Hubmeter	
Brakes	4
Dimensions / Length	254x145x35 cm
Options	
Colour	silver
Coupling	KF20
Colour	
Tyre - Rear	195/50R13c
Tyre - Front	195/50R13c
Lighting	All sides
Tipper Features	
Body Type	Aluminium
Tarps	
Hoist	
Capacity (Cubic Metres)	1.3
Options	["Chassis Tipper"]

